

Current Status of the Claims

This listing of claims will replace all prior versions, and listings, of claims in the application:

What Is Claimed Is:

1. (currently amended) A noise reducing device for a pressurized fluid system comprising:

 a housing comprising an inlet end and an outlet end, said inlet end and said outlet end each comprising at least one orifice for passing said fluid therethrough, said inlet end orifice comprising an inlet face and an outlet face; said inlet end orifice operatively arranged to maintain a backpressure upstream of said inlet end orifice; and,

 a diffusing pack material disposed within said housing, said diffusing pack material maintaining contact with said outlet face of said inlet end orifice, wherein said diffusing pack material obstructs said inlet end orifice and said outlet end orifice.
2. (original) The noise reducing device of Claim 1 wherein said diffusing pack material comprises monofilament wire knitted to form a mesh.
3. (original) The noise reducing device of Claim 2 wherein said mesh is folded upon itself to form a plurality of folded mesh layers.
4. (original) The noise reducing device of Claim 3 wherein said folded mesh layers are compressed against said outlet face to a density of between 35 and 45 pounds per cubic foot.

5. (original) The noise reducing device of Claim 4 wherein said monofilament wire has a diameter between 0.006 and 0.011 inches.

6. (original) The noise reducing device of Claim 5 wherein said monofilament wire is resistant to oxidation.

7. (original) The noise reducing device of Claim 5 wherein said monofilament wire is heat resistant.

8. (original) The noise reducing device of Claim 4 further comprising stiffening means disposed within said folded mesh layers; said stiffening means operatively arranged to maintain the homogeneity of said diffusing pack material density.

[[8]] 9. (currently amended) The noise reducing device of Claim 8 wherein said stiffening means comprises wire screen.

[[9]] 10. (currently amended) The noise reducing device of Claim [[8]] 9 wherein said wire screen is resistant to oxidation.

[[10]] 11. (currently amended) The noise reducing device of Claim [[9]] 10 wherein said

wire screen is heat resistant.

[[11]] 12. (currently amended) The noise reducing device of Claim [[10]] 11 wherein said wire screen comprises stainless steel.

[[12]] 13. (currently amended) A noise reducing device for diffusing a pressurized gas comprising:

 a housing comprising an inlet end and an outlet end; said inlet end and said outlet end each comprising at least one orifice for passing said gas therethrough; said orifice of said inlet end operatively arranged to maintain a backpressure upstream of said inlet end orifice;

 a diffusing pack material disposed within said housing, said diffusing pack material comprising layered, knitted wire mesh;

 at least one stiffener means; said stiffener means comprising wire screen disposed within said pack material,

wherein said diffusing pack material maintains contact with said outlet end and said diffusing pack material obstructs said inlet end orifice and said outlet end orifice.

[[13]] 14. (currently amended) The noise reducing device of Claim [[12]] 13 wherein said layered, knitted wire mesh is resistant to oxidation and heat.

[[14]] 15. (currently amended) The noise reducing device of Claim [[12]] 13 wherein said layered, knitted wire mesh comprises stainless steel.

[[15]] 16. (currently amended) The noise reducing device of Claim [[12]] 13 wherein said wire screen is resistant to oxidation and heat.

[[16]] 17. (currently amended) The noise reducing device of Claim [[12]] 13 wherein said wire screen comprises stainless steel.

[[19]] 18. (currently amended) A noise reducing device for diffusing a pressurized gas comprising:

 a housing comprising an inlet end and an outlet end; said inlet end and said outlet end each comprising at least one orifice for passing said gas therethrough; said orifice of said inlet end operatively arranged to maintain a backpressure upstream of said inlet end orifice;

 a first layer of knitted wire mesh; said first layer disposed proximate said inlet orifice and arranged to obstruct said inlet end orifice;

 at second wire screen layer; said wire screen layer proximate said first layer;

 a third layer of knitted wire mesh;

 a fourth wire screen layer; said fourth layer disposed proximate said outlet end and maintaining contact therewith, wherein said fourth layer is arranged to obstruct said outlet end orifice.

Attorney Docket No. NITP:101US
U.S. Patent Application No. 10/734,053
Reply to Office Action of December 30, 2005
Date: February 28, 2006

[[20]] 19. (currently amended) The noise reducing device of Claim [[19]] 18 wherein said knitted wire mesh and said wire screen layers comprise stainless steel.